

CN2033R

Single Needle, Drop Feed, Zig-Zag, Lockstich Machine

With: Horizontal Axis Transverse Rotary Hook, Reverse Feed, Combination Zig-Zag and Straight Stitcher, Built-In, Bobbin Winder, Needle Position Adjustment, Metal Gears (Hardended Steel), Ideal for Artisan Sewing



Applications

- For sewing light to medium heavy weight fabrics including canvas, cloth, lace, leather and vinyls
- For attaching lace, elastic band, bottom hemming, edge stitching, butted seaming, applique and similar operations
- Federal stitch type 304

Features

- Horizontal axis transverse rotary hook
- Dial zig-zag regulator
- Locking zig-zag width regulator
- Straight stitches when zig-zag set to "0" with straight stitch locking device
- Stitches per minute up to 2500
- Reverse stitching
- Built-in bobbin winder

Specification

Speed, Max (S.P.M.)	2500
Clearence Under	6/25" (6.4mm)
Presser Foot	
Stitch Length	5 s.p.i. (5mm)
Work Space	8 5/16" (211mm)
Needle	135 x 5
Bed Size	7" 15 11/16" (178mm x 398.5mm)
Stitch Type	304
Needle Bar Stroke	1 6/25" (3.15mm)
Stitch Width, Max	11/32" (9mm)



