




HIGHLEAD Highlead GC20638 Series

Two-Needle Compound Feed, Split Needle Bar Lockstitch



Model	GC20638	GC20638-D	GC20638-25	GC20638-25D
Max Sewing Speed	2000 r.p.m.	2000 r.p.m.	1800 r.p.m.	1800 r.p.m
Stitch length	0-9 mm	0-9 mm	0-9 mm	0-9 mm
Needle bar stroke	33.4 mm	33.4 mm	33.4 mm	33.4 mm
Presser foot lift By hand/knee	7 / 13mm			
By hand/Pneumatic			7 / 13mm	
Needle Size	DP x 17 23"			
Rotating hook	Large Hook	Large hook for trimmer	Large Hook	Large hook for trimmer
Needle Gauge	8mm standard 9.5 special		8mm standard, 6.4mm, 9.5mm special	
Motor	370W	220V 550W	370W	220V 550W
	CLUTCH	SERVO	CLUTCH	SERVO
Working Space	254 x 100 mm		635 x 100 mm	

This machine is a new product specially developed for car seat industry, which is designed with split needle bar to be engaged or disengaged for convenient corner stitching, ball bearing for arm shaft and lower shaft, cog belt driving, plunger oil pump for automatic material of heavy weight, such as leather, foam plastic, synthetic fabric, etc and can avoid any displacement. It is a high class equipment for stitching car seats, fabric decorations in cars, shoe uppers of leather or synthetic leather, sports apparatus, office furniture, soft cushion, trunk, bag, etc.

GC20638-25-25D Long arm compound feed split needle bar lockstitch sewing machine is available for stitching car covers, car seats, safety belts, tents, parachutes, gliding parachutes sofa, sails and other large workpieces.

