

PLK-E03BT



SPECIFICATIONS

Stitch Type	Single Needle Lockstitch	Hook	Shuttle/Standard/Bobbin Size A
Sewing Patterns	16 Bartacks Included	X/Y Drive	Rack and Pinion
Sewing Area	(X) 2" x (Y) 1 $\frac{3}{16}$ "	Needle	135x5 Size 18 (Standard)
Max. Sewing Speed	2500 RPM	Work Holder Lift	Max. 15mm
Sewing Speed Selection	200~2000 RPM (10 Steps Variable)		
Feeding System	Intermittent or Continuous	Pattern Input Optional	Touch Screen (PLK-E-PAL)
Stitch Length	0.1~12.7mm	Drive Motor	Limi-Servo (550 Watts)
Pattern Storage	Internal Memory or Floppy Disk	Power (Standard)	220 Volt 3 Phase or Single Phase
Max. Number of Stitches	8,000 Per Pattern	Power	110 Volt (Optional)
Scale Up/Scale Down	10~200% For X and Y Axis	Clamp (Electric)	Single Stage Split Clamp
Measurement	W(1200mm) D(740mm) H(1220mm)	Total Weight (Net)	113kg

NOTE: Sewing speed may be limited by the type of operation, material, or clamp weight.