

PLK-E5050/10050



SPECIFICATIONS

Stitch Type	Single Needle Lockstitch	Hook	Shuttle/Large/Bobbin Size R
Max. Number of Sewing Patterns Possible	255 (Internal Memory) 224 (Floppy Disk)	X/Y Drive	Timing Belt
Sewing Area for 5050	(X) 19 $\frac{11}{16}$ " x (Y) 19 $\frac{11}{16}$ " (500mm x 500mm)	Needle	135x17 Size 18 (Standard)
Sewing Area for 10050	(X) 39 $\frac{3}{8}$ " x (Y) 19 $\frac{11}{16}$ " (1000mm x 500mm)		
Max. Sewing Speed	2000 RPM	Work Holder Lift	Max. 30mm
Sewing Speed Selection	200~2000 RPM (10 Steps Variable)	Presser Foot Lift	Max. 18mm
Feeding System	Intermittent or Continuous	Pattern Input	Touch Screen (PLK-E-PAL)
Stitch Length	0.1~12.7mm	Drive Motor	Limi-Servo (550 Watts)
Pattern Storage	Internal Memory or Floppy Disk	Power	220 Volt 3 Phase or Single Phase
Max. Number of Stitches	8,000 Per Pattern	Power	110 Volt (Optional)
Scale Up/Scale Down	10~200% For X and Y Axis	Clamp (Air)	Cassette Type Adaptor System
Measurement for 5050	W(1390mm) D(1860mm) H(1290mm)	Total Weight (Net)	470kg
Measurement for 10050	W(2105mm) D(1855mm) H(1184mm)	Total Weight (Net)	500kg

NOTE: Sewing speed may be limited by the type of operation, material, or clamp weight. The clamp is not included with these machines.